



BS1054

Garantie Exqua d'Or Grondverf

ALGEMEEN

P	I	-	/
U	W		
	H	P I	/
	P	-	/
	P	.	/
L	T	/	
	T	/	
	H	/	
		/	
	H	/	

APPLICATIEGEGEVENS

B	Kwast of verfroller		
	W	)	/3 /
S	U	/	
B	51		
S	D 27 0 -		/
E	Bepaald bij 23°C en 50% RV		
	T	/3	
	L	/5	
	P	/27	
B	O		6 D
		96 /	
W	H	P H	/



BS1054

Garantie Exqua d'Or Grondverf

TECHNISCHE GEGEVENS

T / 246 0⁴
W / 76 /
H /
W /
I V C 27 /
/) H P H 2
/

OVERIGE INFORMATIE

L /
I 3 /
W 2 3-6 /
P L /

SYSTEEMADVIES

BMH N O P /E
- /W
/

P Hout:
H H P H /
/ H H P H /
M H P I /
Thermisch verzinkt staal en en non-ferro metalen:
H /
B /
I H V /
H H P H /
M H P I /



BS1054

Garantie Exqua d'Or Grondverf

SYSTEEMADVIES

H

Geschilderd hout:

P /
/

L	H	P H	/
H	H	P H	/
M	H	P I	/

Geschilderd staal:

P /
/

L	/	H	V	/
L	H	P H	/	/
H	H	P I	/	/
M				

AANVULLENDE GEGEVENS

NH

21 215EO4: 46OM

E

31 29